



**QC STL PRO-4.8X**  
**QuietCool Stealth Pro Line**

**QC STL PRO-4.8X Specifications**

|  |   |  |
|--|---|--|
| Air Flow   | Hi: 4,280 CFM / Med: 3,500 CFM / Low: 2,361 CFM   |  |
| HVI-916 Airflow (for CA Title 24 New Construction) | Hi: 3,130 CFM / Med: 2,560 CFM / Low: 1,670 CFM   |  |
| Recommended SQFT Coverage @ 2-3 CFM per SQFT       | Covers 1,427 SQFT to 2,140 SQFT   |  |
| Energy Use   | Hi: 408 Watts / Med: 225 Watts / Low: 73.9 Watts  |  |
| Amps   | Hi: 5.16 / Med: 3.00 / Low: 1.07  |  |
| Motor Voltage                                      | 120 VAC, 60 Hz  |  |
| # of Speeds  | 3   |  |
| dBA  | Hi: 47.4 / Med: 41.6 / Low: 33.0  |  |
| Minimum Attic Clearance                            | 36"   |  |
| Duct Diameter                                      | 18"   |  |
| Duct Length  | 9 feet  |  |
| Motor Head Diameter                                | 18 1/2"   |  |
| Motor Head Length                                  | 13 1/2"   |  |
| Dampers  | Barometric Pressurized R5 Dampers   |  |
| Controls (Sold Separately)                         | Included: 8 Hr Electronic Timer & Double 3-way switch<br>Optional: IT-36002 QuietCool RF Wireless Control Kit |  |
| Warranty   | 15 Years  |  |
| Framing  | None Required   |  |
| Joist Cutting                                      | None Required; fits 16" or 24" on center  |  |
| Minimum Suggested Attic Venting                    | 5.71 SQ FT net free area  |  |
| Ceiling Rough Opening                              | 14 1/4" x 30 1/4"   |  |
| Removable Grille Outside Dimension                 | 16" x 32"   |  |
| Shipping Weight                                    | 75 lbs.   |  |
| Box Dimensions                                     | 36" x 22" x 40"   |  |
| In The Box   | -QC STL PRO-4.8X Motorhead<br>-Ceiling Grille<br>-Cut-out Template<br>-Window Locks                           | -Damper Box<br>-9 Foot Duct<br>-Accessory Bag<br>-Controls |



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)